Proposed Dredging of Craven Pond

Three Lakes Association's Evaluation of Anticipated Phosphorus Loading on Lake Bellaire Water Quality

Presented to Bellaire Village Council

July 18, 2007

Dean Branson and Norton Bretz, TLA


Doug Endicott, GLEC


Craven Pond Dredging by the Village of Bellaire




Dredging Scenario Assumptions

- About 80,000 cubic yards sediment to be removed, six-week operation, five days per week
- Five lab tests simulating sediment & phosphorus potentially suspended in pond water during dredging...
 - ® Mix 125 ml sediment + 500 ml pond water
 - ® 212 ug/L phosphorus in surface water after 7 hr settling
- · Phosphorus loading rate during dredging...
 - ® 37.8 kg/day based on 100 cfs (Cedar River) x 212 ug/L
 - 1,600 kg phosphorus into Lake Bellaire in six week
- · Suspended solids from dredging passes over dam, no mitigation







Uncertainties include...

- Duration of the dredging operation, vs 6 weeks
- Actual vs estimated phosphorus release rate, 38 kg/d
- Capability of reducing phosphorus release rate...
 - ® Increasing settling time by raising & lowering dam spillway
 - **®** Using submerged barriers around dredging operation to contain some suspended solids
 - ® Other ideas for reducing mixing of sediment & pond water

Conclusions

- Phosphorus concentration in Lake Bellaire is expected to increase from 4 to 14 ppb during the winter months and then decrease to about 6 ppb (4 ppb is normal) by next spring.
- Water clarity is not expected to be significantly less next summer compared to previous summers.
- Parameters of some concern to be monitored after dredging:
 - **8** Blue-green algae in Lake Bellaire next summer
 - ® Dissolved oxygen near bottom, Lake Bellaire, fall 2008
 - **8** Sediment in Intermediate River
 - Phosphorus in lake midlevel